

IDS Lamps

Elegant, six-colour LED lamps controlled over your IDS network



IDS Lamps can be positioned anywhere on your IDS network – desktops, studio walls or near doorways and entrances, providing an instant visual indication of broadcast status.

Table lamps are manufactured using milled aluminium and opaque plastic, making them solid and attractive. The wall light is made from moulded plastic making it lightweight and suitable for hollow walls and partitions, while its curved lens provides 180° visibility making it ideal for corridors. All lamps connect to your network via Ethernet and, with PoE can be installed quickly and discreetly.

Management of the lamps is straightforward, using the Windows® based configuration software supplied. They support DHCP for automatic acquisition of IP address, but can be configured manually for a static IP if required.

Applications

Use table lamps in studios and voice booths, attach wall lamps outside live areas. Available with single or dual bright LEDs. Lamps with dual LEDs let you assign simultaneous alerts to each lens, for example mic live and telephone ringing warnings or mic live and a flashing cue. Alternatively, both LEDs can signal the same alert.

What is IDS?

IDS is an extendable, network-based control and display system designed specifically for the broadcast industry.

Consisting of dedicated software and hardware devices that use a standard TCP/IP backbone, IDS can be scaled to suit any installation, delivering anything from simple timing and tally information to complex station-wide control functionality via networked displays and intuitive touchscreens.

It integrates with essential broadcast equipment, interfaces with third party control, automation and playout systems, controls cameras, DMX lighting, mixers and many other common devices; while its intuitive software enables simple user configuration and workflow changes.

Key features

- Windows® configuration utility
- Stand-alone USB setup
- Assignable network configuration
- PoE – simplifies installation
- 10/100 RJ45 Ethernet
- Very low power consumption
- CE marked for sale in EU
- 1 year warranty

Key benefits

- Flexible lighting controlled over your IDS network
- Configure bespoke lighting effects using IDS Core
- Bright LEDs for multiple alerts and status warnings
- Control lighting levels using IDS Content Manager

Technical specifications

Construction: Milled aluminium, moulded plastic

Dimensions: H x D (mm) Short table lamp: 230 x 125, Table lamp: 350 x 125, Wall lamp: 75 x 305

Weight: (g) STL: 550, TL: 700, WL: 800

Connectors: Mini USB, RJ45

Power supply: PoE 48V

Power consumption: 12W Peak

Operating temperature: 0°C to +50°C

Approvals: CE